

SMITH ENTERPRISE, INC.
1701 West 10th Street, Suite 14
Tempe, Arizona, 85281
(480) 964-1818, Fax (480) 921-9987
www.smithenterprise.com

VORTEX® MK46/PARA SAW 5.56MM FLASH ELIMINATOR, P/N 1040V

**New enhanced design now supports use of SEI quick-disconnecting sound suppressor.
Works with MK46, Para and Mono Block barrels.**



The world's most effective flash eliminator is now available the 5.56mm MK46 Squad Automatic Weapon (SAW), to include the "Para" version and weapons employing the new "Mono Block" barrel configuration. Based on the combat-proven Vortex® system, the definitive development of the patented Vortex® design now features a 40% increase in structural rigidity. This new version also enables the use our quick disconnecting M249/MK46 DC ("Direct Connect") sound suppressor. The new MK46 model features our patented 15-degree helix, guaranteeing a complete propellant burn and negligible flash, unlike the standard issue closed-end "bird cage" unit or competing straight-flute designs. Right hand helical flutes will not loosen under sustained fire. The aligning of exiting gases with this patented design has been proven to enhance practical accuracy.

The new G6 BFA is machined from 8620 steel and features a hardened 416 stainless steel shaft for long service life. The body of G6 BFA is supplied in a very durable powder coat finish. The robust dimensions, manner of construction and use of high-grade materials offer a quantum improvement over the issue BFA item. Also, a grenade ring is attached to the center shaft to prevent loss in the field. This BFA is suitable for all 5.56mm weapons equipped with the appropriate model Vortex® flash eliminator. This development of a common BFA for 5.56mm issue weapons eliminates the need to maintain multiple BFAs for each weapon in that caliber.



Canadian Army issue 5.56mm Para with MK46/Para Vortex®

SPECS:MK46 Vortex®: Heat-treated 8620 steel, RC 55-60 Internal, RC 35-38 Surface Hardness to depth .006 to .010, 9/16" X 24 TPI (Left), Phosphate Finish, Overall Length 3.175", Diameter .860", Wt. .26 lbs.

Part No. 1040V

MK46 Vortex® Flash Eliminator

Part No. TBA

G6 Blank Firing Adaptor (BFA), cal. 5.56mm NATO

NOTE: Standard M-249 SAW requires p/n 1001BV, which is threaded 1/2X28 TPI (Right).

(Information current as of 12 Sep 05)